



Thermal POS printer series Model: NWE DTP-III 80mm thermal receipt printer with auto cutter

Specification:

| | |
|-----------------------------------|---|
| Printing Method | Thermal line printing |
| Resolution | 203dpi,8dots/mm |
| Character Set | Support User-defined characters GB18030 24X24 ASCII 9X17,12X24 |
| Graphics printing | support dots printing with different densities,support raster bitmap print,support downloaded bit image print |
| Code pages | support simplified&traditional Chinese ,English,Japanese and other 45 kinds of international character sets. |
| Barcode type | UPC-A;UPC-E;JAN13(EAN13);JAN8(EAN8);CODABAR;ITF;CODE39;CODE93;CODE128;QR CODE; |
| Interface | USB/USB+Ethernet/USB+Parallel/USB+Serial+Ethernet/USB+Bluetooth+WiFi |
| Power | DC 24V/2A |
| Cashbox control | RJ11-6P6C Socket,24V |
| Work environment | Temperature: 0~45°C; Dampness:10~80% |
| Storage environment | Temperature: -10~60°C; Dampness:10~90% |
| Paper Width | 79.5± 0.5mm |
| printing width | 72mm |
| Max diameter of paper roll | 80mm |
| Paper cutting | auto cutter |
| Dimension | 195x145x143.3mm |
| TPH life | 100km |
| cutter life | 1,000,000 times |
| Drivers: | Windows(WIN7/WIN8/WIN10/Vista/XP/2000) Ubuntu 12.04 32/64 Ubuntu 14.04 32/64 MAC OS |
| Printing command | Compatible with POS/ESC command set |



Feature

- ★ detection function:paper end
- ★ **IP address automatic allocation,printer name access support (only for Ethernet port model)**
- ★with auto cutter
- ★ High speed、high life、high quality、low repair rate, apply to all sorts of business software
- ★Exquisite design and easy to use
- ★Low noise,high-speed printing
- ★with cash drawer interface
- ★Light in weight and smart in shape
- ★Easy paper loading design, widely used in various industries

Application:

- ◆ Restaurants
- ◆ Department Stores
- ◆ Kitchen
- ◆ Convenience Stores
- ◆ Specialty Retail
- ◆ Super market
- ◆ Medical Shop